

Specification



K33-150

Seed cane soaking liquid before planting.

1. Horse Power requirements (HP) : 120
2. Single row Billet planter (Billet from Combine Harvester)
3. Capacity of Load (kg) : 1,000
4. Fertilizer Tank Capacity (kg) : 160 (2 Tank and 80 kg (Tank))
5. Seed cane soaking liquid before planting.
6. Sink row and big open groove.
7. 2 Sweep soil discs
8. Have long roller (Single)
9. Mounting : 3 Point hitch (CAT II)
10. Efficiency 20-25 : (Rai/Day)

Specification Data Sugar cane planter (Double Row)

Technical Data	Sugar Cane Planter(Double Row)					Trailer
Description	K33-160	K33-180	K33-190	K33-220	K33-150	K40-2000
Power Requirement (HP)	40-50	55-90	55-90	55-90	120	40-90
Long of Billet (cm)	30-40	30-40	30-40	30-40	-	-
Type of Feed	Vertical	Vertical	horizontal	Vertical	Top	-
Capadty of load	600-700	700-900	load by Trailer	900-1,100	1,000	2,000
Fertilizer Tank Capacity(kg)	80	80	150	80	150	-
Distance between row (cm)	27	33	33	33	-	-
sweep soil disc (pc)	2	2	2	2	2	-
Mounted	Cat I and Cat II	Cat II	Cat II	Cat II	Cat II	-
No. of steel wheels	2	2	2	2	2	4 Tyre size 7.50-16
Effideny (Rai/Day)	9-11	10-12	20-25	12-15	20-25	-

The company reserves the right to make changes in specification without prior notice.



GOOD GROW ACCURATE REGULARLY



KAMOL INDUSTRY CO., LTD.

Office : 63 Soi Srimuang Anusorn, Suthisarn Rd, Dindaeng Bangkok 10400 Tel. (02)277-0589, 277-5713,

277-6127, 277-7052-4 FAX: (02)276-1183

FACTORY: 119 THEPHARAK RD, K.M.21, BANGSAOTHONG, SAMUTPRAKAN 10540

Tel. (02)-315-4161-4 Fax: (02)315-4160

E-mail: kmt@kamolindustry.com www.kamolindustry.com

Distributor :



ผลิต-จัดจำหน่ายโดย บริษัท กมลอินดัสตรี จำกัด

สำนักงาน : 63 ซอยสีม่วงอนุสรณ์ ถนนสุทธิสารฯ แขวงดินแดง เขตดินแดง กรุงเทพฯ 10400

โทร. (02)277-0589, 277-5713, 277-6127, 277-7052-4

แฟกซ์ (02)276-1183

โรงงาน : 119 ถนนพารักย์ กม.21 ด.บางเสาธง กิ่ง อ.บางเสาธง สมุทรปราการ 10540

โทร. (02)-315-4161-4 แฟกซ์ (02)315-4160

E-mail : kmt@kamolindustry.com www.kamolindustry.com

SUGAR CANE PLANTER "KMT"

SPECIFICATION



K33-160

Specification

1. Horse Power requirements (HP) : 40-45
2. Length of Billet (cm) : 30-40
3. From Top Feed (Vertical)
4. The big basket high 89 cm. for easy put seed cane
5. Capacity of Load (kg) : 600-700
6. Fertilizer Tank Capacity (kg) : 80 and made by Stainless.
7. Fertilizer tank fix in front of basket and not load and Fertilizer can put before seed cane
8. Distance between Row (cm) : 27
9. Wheel drives the Blade cutter and feed fertilizer by wing drive wheel (steel wheel.)
10. 2 sweep soil discs
11. Have long roller (single or)
12. Mounting : 3 point hitch (CAT I and CAT II)
13. Efficiency (Rai/Day) : 9-11

OPTION Pump and Nozzle for Double Row
Pipe and Tank 1000 Liter



K 33-180

Specification

1. Horse Power requirements (HP) : 55-90
2. Length of Billet (cm) : 30-40
3. From Top Feed (Vertical)
4. Capacity of Load (kg) : 700-900
5. Fertilizer Tank Capacity (kg) : 80 and made by Stainless.
6. Distance between Row (cm) : 33
7. Wheel drives the Blade cutter and feed fertilizer by wing drive wheel (steel wheel.)
8. 2 sweep soil discs
9. Have long roller (single) or Short Roller (Twin) (one or the other)
10. Mounting : 3 point hitch CAT II
11. Efficiency (Rai/Day) : 10-12

OPTION Pump and Nozzle for Double Row
Pipe and Tank 1000 Liter

Specification

1. Horse Power requirements (HP) : 55-90
2. Length of Billet (cm) : 30-40
3. From Top Feed (Horizontal) and with Trailer.
4. Capacity of Load (kg) : 2,000
5. Fertilizer Tank Capacity (kg) : 150
6. Distance between Row (cm) : 33
7. 2 sweep soil discs
8. Have long roller (single)
11. Mounting : 3 point hitch (CAT I and CAT II)
10. Efficiency (Rai/Day) : 20-25



OPTION Pump and Nozzle for Double Row
Pipe and Tank 1000 Liter



K33-220

Specification

1. Horse Power requirements (HP) : 55-90
2. Length of Billet (cm) : 30-40
3. From Top Feed (Vertical)
4. The big basket high 89 cm. for easy put seed cane
5. Capacity of Load (kg) : 900-1,100
6. Fertilizer Tank Capacity (kg) : 80 and made by Stainless.
7. Fertilizer tank fix in front of basket and not load and Fertilizer can put before seed cane down.
8. Distance between Row (cm) : 33 (Suitable for Combine Harvester.)
9. Wheel drives the Blade cutter and feed fertilizer by wing drive wheel (steel wheel.)
10. 2 sweep soil discs
11. Have long roller (single) or Short Roller (Twin) (one or the other)
12. Mounting : 3 point hitch CAT II
13. Efficiency (Rai/Day) : 12-15

OPTION Pump and Nozzle for Double Row
Pipe and Tank 1000 Liter